



Seismic Array Constraints on reach-scale bedload transport



Motivations for quantitative measures of stream dynamics from outside the channel

Sediment transport by streams generally is the rate-limiting process for landscape evolution. Much work done during extreme discharge events, difficult to access the bed.




Management of watersheds




Sediment transport in regulated watersheds – balancing multiple uses and conserving habitats



The focus here is bedload



Flume example



Because it's otherwise hard to measure the bottom of a river while it is actively being carried away, and rock collisions should be a tractable target for seismology

What can we measure?

It's particularly difficult/expensive to measure bed-load transport, but it is estimated to comprise ~2 to >50% of total sediment mass flux



An accurate but costly way to study bed-load transport in Switzerland, at the Erlenbach (e.g., Rickenmann et al., 2012)


Not feasible to do this for many rivers...

Other common methods such as traps and force plates still not easy/cheap




Listening to fluvial processes with seismology

- Some pioneering observation and modeling efforts



Burtin et al., 2008 – Trisuli River, Nepal

More bedload for given discharge at beginning of wet season? Possible changes in turbulence (Roth et al., 2017)?



Tsai et al., 2012 – analytic model of Hertzian impacts along a bedrock channel


Listening to fluvial processes with seismology

Array with several L-22 seismometers in Grand Canyon



(Schmandt et al., 2013)

Array with ~100 nodes at the Trinity River in northern CA



(Schmandt et al., 2017)

Listening to fluvial processes with seismology

Array with several L-22 seismometers in Grand Canyon



Near threshold for any bedload movement, controlled floods designed to stimulate suspended load transport to maintain sandbars.

Good place to test if seismometers can detect onset and termination of small bedload flux.



(Schmandt et al., 2013)

Node array at the Trinity River in northern CA



Goal is to move as much bedload as possible with limited reservoir water. Controlled floods are augmented by gravel supply augmentation.


Good place to test seismic signal of higher bedload flux (~1000 tons/day) and response time scales to supply perturbations



(Schmandt et al., 2017)

Trinity River Restoration Program



- Multi-agency effort to restore the salmon fishery, physical geomorphology led by U.S. Bureau of Reclamation
- First impacted by hydraulic mining in 1800's, leaving abundant gravel tailings
- Later dam regulated discharge limited natural channel restoration since 1960
- Restoration effort ongoing since early 2000's, includes controlled floods for mechanical modification of the river channel



(Gaeuman et al., 2017)

Key Collaborators: David Gaeuman, Robert Stewart of USBR in Weaverville, CA (www.trrp.net)

Trinity River Restoration Program



Physical sampling of bedload

Repeat bathymetry

Controlled gravel augmentation

Controlled flooding

(Gaeuman, 2011)

Key Collaborators: David Gaeuman, Robert Stewart of USBR in Weaverville, CA (www.trrp.net)

1. Unnatural channel constrictions due to gravel levees and tailings piles from hydraulic mining
2. Decades of low discharge due to water diversion for Great Valley farming



Photo 69. Carrville Gold Company Dredge, Trinity River District. This photo was taken on the upper Trinity River in Trinity County in 1940.
Photo courtesy of Yuba Consolidated Industries.

TRRP goals include stimulating bedload transport to help restore channel's salmon habitat




A section of the alternating bar gravel bed river that is in a more natural state

Underwater video
observations of
gravel transport

Highest discharge
is similar for the
2015 flood
studied with the
node array

Trinity River Node Array in 2015



(Schmandt et al., 2017 Geology)

Lowden Ranch Array (largest of 4 sub-arrays)

~30 m spacing along a 700-m reach of the Trinity River

Gravel injection site near upstream end and physical sampling transect near the middle


Only vertical component
2-week battery life
1st generation Fairfield Zland

Rented from NodalSeismic,
service company from Long
Beach, CA




Autonomous seismographs (nodes):

- cable-free
- GPS clock
- 24-bit digitizer
- 2-week battery life
- hard drive capacity




Fairfield Nodal Zland,
1st generation

Rented from NodalSeismic,
service company from Long
Beach, CA




Geophone response peak at 10 Hz

What frequency range is excited by bedload transport?





Gravel supply augmentation during constant water discharge directly identifies the shape of the local bedload spectrum



Difference between S2 and S3 spectra shows bedload dominantly affects greater than 20 Hz spectrum



(Schmandt et al., 2017 Geology)




Smooth variations in low-frequency (<12 Hz) correlated with discharge



High frequency (>20 Hz) responds to gravel augmentation for ~10 hours



After >10 hours the downstream segment produces about half the seismic power of the upstream segment

Spatial variability in bathymetric change and seismic amplitudes



Before flood and gravel injection



After 2 gravel injections and flooding



Steady alternating bar morphology with ~ 3 m of relief was not strongly modified during the high discharge event.

Migrating bedforms during event have maximum relief of ~ 0.3 m



Gravel bed channel produces ~15-20 dB lower power compared to predictions for bedrock channel signal



Predicted bedload flux constrained by physical sampling and bathymetry changes, uses analytical model of Tsai et al. [2012]



Seismic constraints on bedload transport at the Trinity River

- Time scale to adjust to supply perturbation, ~7-10 hours favors shorter higher discharge events
- Change in seismic amplitude coincident with along stream change from migrating gravel dunes to plane-bed saltation
- Potential to constrain dissipation of impact energy in alluvial versus bedrock channel segments



Seismic constraints on bedload transport at the Trinity River

Questions?



Hammer source amplitude decay

